

SQUARE KELLY DATA

Nominal Size in.	Length ft L	Length ft LD	Top Upset LH Connection	Top Upset OD in.	Bottom Upset RH Connection	Bottom Upset OD in.	Bore d in.	Drive Section DFL in.	Drive Section DCC in.	Weight lbs	Weight kg
3 1/2	40	37	6 5/8 REG	7 3/4	NC 38	4 3/4	2 1/4	3 1/2	4.437	1 323	600
3 1/2	40	37	4 1/2 REG	5 3/4	NC 38	4 3/4	2 1/4	3 1/2	4.437	1 213	550
4 1/4	40	37	6 5/8 REG	7 3/4	NC 46	6 1/4	2 13/16	4 1/4	5.500	1 852	840
4 1/4	40	37	6 5/8 REG	7 3/4	NC 50	6 3/8	2 13/16	4 1/4	5.500	1 852	840
4 1/4	40	37	4 1/2 REG	5 3/4	NC 46	6 1/4	2 13/16	4 1/4	5.500	1 742	790
4 1/4	40	37	4 1/2 REG	5 3/4	NC 50	6 3/8	2 13/16	4 1/4	5.500	1 742	790
5 1/2	40	37	6 5/8 REG	7 3/4	5 1/2 FH	7	3 1/4	5 1/4	6.750	2 800	1 270

HEXAGONAL KELLY DATA

Nominal Size in.	Length ft L	Length ft LD	Top Upset LH Connection	Top Upset OD in.	Bottom Upset RH Connection	Bottom Upset OD in.	Bore d in.	Drive Section DFL in.	Drive Section DCC in.	Weight lbs	Weight kg
3 1/2	40	37	6 5/8 REG	7 3/4	NC 31	4 1/8	1 3/4	3 1/2	3.937	2 403	575
3 1/2	40	37	4 1/2 REG	5 3/4	NC 31	4 1/8	1 3/4	3 1/2	3.937	1 168	530
4 1/4	40	37	6 5/8 REG	7 3/4	NC 38	4 3/4	2 1/4	4 1/4	4.781	1 951	885
4 1/4	40	37	4 1/2 REG	5 3/4	NC 38	4 3/4	2 1/4	4 1/4	4.781	1 852	840
5 1/4	40	37	6 5/8 REG	7 3/4	NC 46	6 1/4	2 13/16	5 1/4	5.900	2 227	1 010
5 1/4	40	37	6 5/8 REG	7 3/4	NC 50	6 3/8	3 1/4	5 1/4	5.900	2 227	1 010
5 1/4	40	37	6 5/8 REG	7 3/4	NC 50	6 3/8	2 13/16	5 1/4	5.900	2 227	1 010
6	40	37	6 5/8 REG	7 3/4	5 1/2 FH	7	3 1/2	6	6.812	2 403	1090